



Volcan RS

K105 | L80

	340/65R18	280/70R18	320/65R18	250/85R20	300/70R20
	with adjustable rim	with adjustable rim	with adjustable rim	with adjustable rim	with adjustable rim
A	343	282	320	245	286
B	899	849	873	940	942
C	1098/1538	1098/1538	1098/1538	1046/1588	1134/1618
D	1441/1881	1380/1820	1441/1881	1291/1833	1420/1904

	320/70R20	340/65R20	31x15.50-15 XTC	31x15.50-15 STG	13.6-16 Garden
	with adjustable rim	with adjustable rim	with fixed rim	with fixed rim	with fixed rim
A	316	343	368	394	391
B	975	958	800	800	968
C	1134/1618	1134/1618	1260/1374	1260/1374	1240/1400
D	1450/1934	1477/1961	1628/1742	1654/1768	1631/1791

Dimensions Volcan K105 L80 RS (mm):							
E	F	G	H	I min/max	L min/max	M min/max	N min/max
1348	1495	932	3775	184/294	2254/2364	2070/2180	2139/2249



TECHNICAL FEATURES	Volcan K105 RS	Volcan L80 RS
ENGINE	Kubota V3800 CR-TE4	Kohler KDI 2504 TCR
Number of cylinders	4 in-line	4 in-line / 16 valves
Displacement (cm ³)	3,769	2,482
Intake	Turbo	Turbo / Intercooler
Fuel system	Direct injection "Common rail"	Direct injection "Common rail" - 2000 bar
Emission level	Stage 3B	Stage 3B
Balancing	Counter-balance shafts	Counter-balance shafts
Power (kW/HP)	72.1 / 98	55.4 / 75.3
Rated speed (rpm)	2,400	2,300
Maximum torque (Nm/rpm)	330 / 1,500	300 / 1,500
Speed management	Electronically regulated with a console with functions: increase and decrease of engine speed, memorize and recall a particular speed or switch off the electronic throttle and go to the minimum idle speed	
Cooling	Liquid	
Tank capacity (lt)	54	
CHASSIS	Swinging integral chassis OS-FRAME with steering wheels	
DRIVE	Four-wheel drive. Front-wheel drive disengagement with electro-hydraulic control	
TRANSMISSION	32 speeds synchronized gearbox: 16 FWD and 16 REV with synchronized reverser	
POWER SHUTTLE EASYDRIVE® (optional)	Electro-hydraulic power shuttle electronically actuated with the lever (with 3 position FWD-N-REV) installed on the left of steering wheel. Possibility to choose from 5 levels of reactivity	
Transmission clutch	Multidisc in oil bath electronically-managed and proportional hydraulic control with PRO-ACT System	
DIFFERENTIAL	Front and rear. Differential lock: front and rear simultaneously or only rear with electro-hydraulic control	
AXLES	Front and rear with epicyclic reduction units. Front axle, oscillating in the middle (approx. ±15°)	
REAR PTO	Independent from the gearbox and synchronized with forwarding speed. Engageable under load with brake in disengaged position	
PTO clutch	Multidisc in oil bath with electro-hydraulic control	
PTO rotation speed (rpm)	Standard: 540/540E - Optional: 540/1,000	
HYDRAULIC SYSTEM	Double circuit with independent pumps and heat exchanger	
Flow rate to the hydroguide and the electro-hydraulic controls (lt/min)	33	
Flow rate to the lift and the control valves (lt/min)	30 (optional oversized pump with flow rate 49 lt/min)	
Maximum hydraulic pressure (bar)	180	
REAR CONTROL VALVES	Mechanical control	
Standard	2 double acting	
Optional and in addition to the standard ones	1 single acting and 1 double acting or 1 double acting and 1 double acting with float	
Joystick (optional)	With proportional electronic control of lifts and control valves consisting of: 1 single acting with adjustable flow and free return, 5 double acting (replacing the standard ones) and oversized pump 49 lt/min. Potentiometer to change the sensibility of the joystick	
ELECTRIC SYSTEM	Battery 100 Ah / 12 V - Alternator 95 A	
Rear power outlets	7 pin and 3 pin	
REAR LIFT	Standard: by two external rams - Optional: position and draft control	
Three-point hitches	Standard: standard couplers cat. 1 and 2. Optional: quick couplings cat. 1 and 2, arms with adjustable length or quick couplings, L-shaped, cat. 1 and 2, arms with adjustable length and hooks with adjustable width.	
Three-point tie bar	Standard: with manual adjustment - Optional: hydraulically controlled upper link and tie rod link arm	
Ball joint lifting capacity (kg)	2,300	
FRONT LIFT (optional)	By two external rams with front protection and 2 double acting control valves with free return	
Three-point hitches	Rigid with quick couplings cat. 1	
Lifting capacity (kg)	800	
DRIVING PLATFORM	Reversible with platform suspended on silent block. Suspended pedals mounted on rotating control column	
Steering wheel	With adjustable inclination	
Seat	With gas spring for easy tipping, safety belt and 'man on board sensor'. Standard: comfortable sprung seat, adjustable according to the driver's weight - Optional: 'Kab Seating' or 'Grammer' pneumatic seat	
SERVICE BRAKES	Oil bath discs with hydrostatic control, acting on the four wheels with automatic engagement of the 4-wheel drive	
Parking brake	Automatic and independent Brake-Off acting as emergency brake with proportional action	
STEERING	Hydrostatic steering acting on front wheels. Flow deviator for steering unit	
SAFETY	Standard: front homologated roll-bar, with gas springs for an easy lowering and liftn	
CABIN (optional)	Homologated and sound-proof with monocoque body fitted on silent-block, beacon lamp and fabric covered seat. With ventilation, heating system and air conditioning. Available with standard or conical structure	
INSTRUMENT PANEL	With multi-function colour and digital display complete with: hour counter, battery voltage, fuel consumption, DPF level, simultaneous reading of engine speed, forwarding speed and PTO speed. Warning lights and acoustic alarm	With multi-function colour and digital display complete with: hour counter, battery voltage, fuel consumption, simultaneous reading of engine speed, forwarding speed and PTO speed. Warning lights and acoustic alarm
TYRES (standard)	280/70R18	
Optional	340/65R18 * 320/65R18 * 250/85R20 * 300/70R20 * 320/70R20 * 340/65R20 * 31x15.50-15 XTC or STG * 13.6-16 Garden	
TOW HOOKS (standard)	Rear CUNA and front	
Optional	Rear tow hook: EC approved or EC approved (Slider type) or CUNA (Slider type)	
WEIGHT in order of speed	2,385	2,315
With roll-bar (kg)	2,530	2,460
OPTIONAL	Front bumper, Beacon lamp, Front weight, Weights for wheels, Active carbon filter for cabin	